



FAMILY OF REMOTE USB HUBS



ANYWHEREUSB PLUS

Connect USB peripheral devices anywhere on a Local Area Network (LAN) without a locally-attached host computer

IoT business automation requires communication with various IT assets and peripherals located across an enterprise. AnywhereUSB® Plus remote USB hubs give users the simplest and most direct connection options for existing equipment with a variety of USB 3.1 Gen 1 port options. It has two built-in power supplies and Gigabit Ethernet support for failover redundancy and network bonding with SFP+ modules for higher speeds or fiber networks.

AnywhereUSB 24 Plus is rack mountable with 24 USB 3.1 Gen 1 ports, while AnywhereUSB 8 Plus and AnywhereUSB 2 Plus are desktop or panel mountable units with eight or two ports, respectively, and support for Gigabit Ethernet.

Anywhere USB can be coupled with Digi Remote Manager®, a web-based device configuration and security management platform, to help users reduce downtime. An intuitive user experience makes installation smooth and easy; with quick setup and configuration to monitor and maintain larger installations of remote Digi and third-party devices, such as cellular routers.

For enterprise and industrial customers who need remote or local USB ports and the higher speeds of USB 3.1 Gen 1 and Gigabit Ethernet, Digi AnywhereUSB Plus products give you an industry-leading connectivity solution.


FEATURES AND BENEFITS

- Network-attached USB hubs easily connect USB peripheral devices to a PC from remote or virtual hosts
- Ideal for connecting USB devices over the network in virtualized environments such as VMware®
- AnywhereUSB 24 Plus is rack mountable with two built-in power supplies and two Ethernet connections for failover redundancy
- Access and monitor USB and serial devices over TCP/IP connection
- Includes Digi Remote Manager® cloud-based management platform to deploy, monitor manage and maintain a suite of peripherals and devices

RELATED PRODUCTS



APPLICATION EXAMPLE




SPECIFICATIONS	ANYWHEREUSB 2 PLUS	ANYWHEREUSB 8 PLUS	ANYWHEREUSB 24 PLUS
CELLULAR			
MODULE SUPPORT	-	(1) Digi CORE modem compliant socket	(1) Digi CORE modem compliant socket
SOFTWARE AND MANAGEMENT			
REMOTE MANAGEMENT	Digi Remote Manager® (cloud based)		
LOCAL MANAGEMENT	WebUI (HTTP/HTTPS); CLI (SSH)	WebUI (HTTP/HTTPS); CLI (Console, SSH)	WebUI (HTTP/HTTPS); CLI (Console, SSH)
MEMORY	512MB RAM, 4GB flash (eMMC)	2GB RAM, 4GB flash (eMMC)	2GB RAM, 4GB flash (eMMC)
NETWORK			
ETHERNET	(1) RJ-45; 10/100/1000 Mbps (auto-sensing)	(1) RJ-45; 10M/100M/1G/10G Ethernet	(2) RJ-45; 10M/100M/1G/10G Ethernet
SFP+	-	(1) SFP+ socket	(2) SFP+ sockets
CONNECTORS			
CONSOLE	-	(1) DB09M; RS232 DTE	
USB	(2) USB 3.1 Gen 1 Type A	(8) USB 3.1 Gen 1 Type A, USB 3.1 Type A x2, USB 3.0 Type A x6	(24) USB 3.1 Gen 1 Type A, USB 3.0 Type A
PHYSICAL			
DIMENSIONS (L X W X H)	4.6 in x 2.9 in x 1.2 in (118 mm x 74 mm x 30 mm)	10 in x 6 in x 1.75 in (260mm x 160 mm x 44.45 mm)	17.75 in x 10 in x 1.75 in (450.85 mm x 255 mm x 44.45 mm)
WEIGHT	0.84 lb (0.38 kg)	3.48 lb (1.58 kg)	10.36 lb (4.7 kg)
STATUS LEDS	(2) Ethernet, 2 (x1) USB, power	(2) Ethernet, (2) SFP+ 8 (x1)USB, power, fan, user, (3) future Wi-fi/WWAN	2 (x2) Ethernet, 2 (x2) SFP+, 24 (x1) USB, 2 (x1) PSU, 2 (x1) fan, user, (3) future Wi-fi/WWAN
POWER REQUIREMENTS			
POWER INPUT	5V, 5A max	12V DC, 12A max	100-240V 3A Max (2 supplies for redundancy)
POWER CONSUMPTION	25 watts max	98.5 watts max	157.7 watts max
ENVIRONMENTAL			
OPERATING TEMPERATURE	32 °F to +104 °F (0 °C to +40 °C)	32 °F to +131 °F (0 °C to +55 °C)	32 °F to +131 °F (0 °C to +55 °C)
RELATIVE HUMIDITY	5% to 95% (non-condensing)	5% to 95% (non-condensing)	5% to 95% (non-condensing)
APPROVALS			
BLUETOOTH	-	Bluetooth BLE 4.2	
SAFETY	UL 60950, CSA 22.2 No. 60950, EN60950, EN62368	UL/EN60950, UL/EN62368 and CSA 22.2	UL 60950, CSA 22.2 No. 60950, EN60950, EN62368
EMISSIONS/IMMUNITY	CE, FCC Part 15 Class B, AS/NZS CISPR 22, EN55024, EN55032	CE, FCC Part 15 Class B, AS/NZS CISPR 22, EN55024, EN55032	CE, FCC Part 15 Class B, AS/NZS CISPR 22, EN55024, EN55032
WARRANTY			
PRODUCT WARRANTY	5 years		

ENTERPRISE SOFTWARE	DESCRIPTION
PROTOCOL SUPPORT	HTTPS, FTP, SFTP, SSL, SMTP, SSH and CLI for web management; remote management via Digi Remote Manager
SECURITY/VPN	TLS 1.2, SSH, HTTPS
ROUTING/FAILOVER	Ethernet bonding (only for AnywhereUSB 24 Plus)
OTHER PROTOCOLS	DHCP

PRODUCT IMAGES

ANYWHEREUSB 2 PLUS FRONT



ANYWHEREUSB 2 PLUS BACK



ANYWHEREUSB 8 PLUS FRONT



ANYWHEREUSB 8 PLUS BACK



ANYWHEREUSB 24 PLUS FRONT



ANYWHEREUSB 24 PLUS BACK



PART NUMBERS	DESCRIPTION
ANYWHEREUSB 2 PLUS MODEL	
AW02-G300	AnywhereUSB 2 Plus; dual USB 3.1 Gen 1 Ports, single 10M/100M/1G Ethernet, 5VDC
ANYWHEREUSB 8 PLUS MODEL	
AW08-G300	AnywhereUSB 8 Plus; eight USB 3.1 Gen 1 Ports, single 10M/100M/1G/10G Ethernet, single SFP+, 12VDC
ANYWHEREUSB 24 PLUS MODEL	
AW24-G300	AnywhereUSB 24 Plus; 24 USB 3.1 Gen 1 Ports, dual 10M/100M/1G/10G Ethernet, dual SFP+, dual power 100-240VAC

ACCESSORIES	DESCRIPTION
76000965	AC Power Supply - Extd Temperature, Universal plugs (US, EU, UK, AU) to 5VDC - 2.5mm locking barrel plug

FOR MORE INFORMATION
PLEASE VISIT WWW.DIGI.COM

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2018 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91004384
A2/219

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL GERMANY
+49-89-540-428-0

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn

